


SPECIFICATIONS

| Size | Metric | British |
|---------------------------------|-------------|------------------|
| Max. Working Height | 18.16m | 59ft 7in |
| Max. Platform Height | 16.16m | 53ft |
| Max. Operating Range(+0.6m) | 11.42m | 37ft 6in |
| Max. Platform Range | 10.82m | 35ft 6in |
| Overall Length(Stowed) A | 8.40m | 27ft 7in |
| Overall Length(Transport) | 6.48m | 21ft 3in |
| Overall Width(Stowed) B | 2.33m | 7ft 8in |
| Overall Height(Stowed) C | 2.49m | 8ft 2in |
| Overall Height(Transport) | 2.60m | 8ft 6in |
| Platform Size(Length×Width) | 1.83m×0.79m | 6ft×2ft 7in |
| Turntable Tailswing | 1.24m | 4ft 1in |
| Ground Clearance D | 0.31m | 1ft |
| Wheelbase E | 2.30m | 7ft 7in |
| Turning Radius(Inside/Outside) | 2.92m/4.49m | 9ft 7in/14ft 9in |
| Tyres | 315/55D20 | 315/55D20 |



| Performance | | |
|----------------------|----------------|----------------|
| S.W.L | 250kg | 551lb |
| Max. Occupants | 2 | 2 |
| Gradeability | 40% | 40% |
| Travel Speed(Stowed) | 6.0km/h | 3.7mph |
| Travel Speed(Raised) | 1.1km/h | 0.7mph |
| Max. Working Slope | X-5°/Y-5° | X-5°/Y-5° |
| Turret Rotation | 360°Continuous | 360°Continuous |
| Platform Rotation | 180° | 180° |
| Jib Movement | 132° | 132° |

| Weight | | |
|----------------|--------|---------|
| Overall Weight | 6830kg | 15058lb |

| Power | | |
|----------------|---------------------|---------------------|
| Diesel Engine | FIRMAN AN192F/7.6kW | FIRMAN AN192F/7.6kW |
| Battery | 48V/320Ah | 48V/320Ah |
| Charger | 48VDC/60A | 48VDC/60A |
| Driving Motor | 34VAC/9kW | 34VAC/9kW |
| Lifting Motor | 34VAC/13kW | 34VAC/13kW |
| Diesel Tank | 30L | 7.9gal |
| Hydraulic Tank | 145L | 38gal |



Range Of Motion



FEATURES

Standard Items

- 1.50m (4ft 11in) Jib
- Front Oscillating Axle
- Two-Wheel Steering
- Four-Wheel Drive
- Self-Leveling Platform
- 180° Left And Right Swing Platform
- Proportional Joystick Controls
- Thumb Rocker Steer
- Drive Enable
- AC Power Cord To Platform
- Tilt Alarm
- Descent Alarm
- Flash
- Horn
- Hour Meter
- Integral Integrated Special Drive Axle For Construction Machinery
- 360° Continuous Turntable Rotation
- Positive Traction Four Wheel Drive
- Platform Load Sense System
- Fault Diagnosis System
- Operator Anti-crushing Protection System
- Harsh Environment Kits
- 12V DC Auxiliary Power
- Battery 48V/320Ah
- Driving Motor 9kW 4834rpm
- Lifting Motor 13kW 1855rpm



Telescopic
Boom-BT



Working
Height-18m



Jib



Hybrid-H



Rough
Terrain-RT



Elevated Platform Services

40 Hands Road, Middleton, Christchurch
P. 0800 3773979
E. office@epsnz.co.nz
epsnz.co.nz

