



SPECIFICATIONS


Metric	British
8.00m	26ft 3in
6.00m	19ft 8in
1.39m	4ft 7in
0.80m	2ft 8in
1.99m	6ft 6in
0.73m×0.75m	2ft 4.7in×2ft 6in
0.53m	1ft 9in
0.06m	2in
0.019m	1in
1.07m	3ft 6in
0/1.55m	0/5ft 1in
Ф323×100mm	Φ1ft 1in×4in
	8.00m 6.00m 1.39m 0.80m 1.99m 0.73m×0.75m 0.53m 0.06m 0.019m 1.07m 0/1.55m


Performance			
S.W.L	159kg	350lb	
Max. Occupants	1	1	
Gradeability	25%	25%	
Max. Working Slope	X-1.5° Y-3°	X-1.5° Y-3°	
Travel Speed(Stowed)	4km/h	4km/h	
Travel Speed(Raised)	1.1km/h	1.1km/h	
UP/Down Speed	23/25sec	23/25sec	

Weight		
Overall Weight	1285kg	2832lb

Power			
Battery	2×12V/115Ah	2×12V/115Ah	
Charger	24V/15A	24V/15A	
Driving Motor	2×24VDC/1kW	2×24VDC/1kW	
Lifting Motor	24VDC/2kW	24VDC/2kW	











FEATURES

Standard Items

- · Cylinder Holding Valve
- · Emergency Stop Button
- Two Controllers Operation
- · Emergency Lowering System
- · Leveling Sensor
- · Forklift Pockets
- · All Motion Alarm
- Transport Tie Hole
- · Battery Charge Indicator
- · Electric Limit Switch
- · Automatic Pothole Protection
- · Drivable At Full Height
- · Overload Sensor With Alarm
- · Onboard Diagnostic System
- · Flashing Beacon

Additional Items

· AC Power to Platform





104 Carbine road, Mount Wellington 0800 DINGLI (346 454) E. Brendan@accessspecs.co.nz

www.accessspecs.co.nz



